

## Erosion and Sediment Controls

1. Erosion control measures shall be maintained at all times.
2. Erosion control measures shall be installed as per the approved grading & erosion control plans.
3. All operational storm drain inlets shall be protected from sediment inflow.
4. Sediment control measures (traps, filters, barriers, etc.) shall be maintained at all times.
5. Temporary soil stock and other stock piled granular materials shall be kept covered, contained or bermed.
6. Sediment-laden runoff shall not flow under, around or through diversion structures.
7. Sediment, sediment-laden runoff or dewatering effluent shall not flow off the site.
8. Sediment, debris or mud shall not be deposited or tracked onto public roads or rights-of-way.
9. Seeded or landscaped areas shall be maintained to provide effective ground cover.

## Chemical and Waste Controls

1. All chemicals (paints, fuels, concrete mix, fertilizers, etc.) shall be properly stored to prevent storm water contamination.
2. All waste products (building materials, wood, sheet metal, broken concrete or paving, paints, etc.) shall be disposed of or recycled properly.
3. All contaminated waters generated during construction shall be properly contained, treated and or disposed of.
4. All storm drain inlets in the vicinity of the site shall be protected from inflow during saw-cutting, sealing, paving, and building washing operations.
5. All heavy equipment shall be parked in a designated area, well away from storm drain inlets.
6. All equipment repaired or maintained on site, shall have drip pans, absorbent pads, berms or other methods used to prevent contamination of soil runoff.
7. A spill response plan shall be in place and all spills shall be cleaned up properly and promptly using dry cleaning methods.
8. Trash receptacles shall be provided for containing solid wastes generated on site, and shall be covered during the rainy season. "
9. All chemical spills or leaks (stains, sludge, etc.) on site shall be taken care of immediately.
10. Chemicals, contaminated runoff, litter, blowing debris or dust shall be properly maintained on site and removed appropriately.
11. Chemical wastes, slurries, wash waters, vehicle fluids, or other discharges shall be handled appropriately and not allowed to enter storm drain inlets.
12. Lawn clippings, pruning waste or yard waste shall not be disposed of in the street, gutters or storm drain inlets.